



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

| APPLICATION NO. | FILING DATE | FIRST NAMED INVENTOR | ATTORNEY DOCKET NO. | CONFIRMATION NO. |
|-----------------|-------------|----------------------|---------------------|------------------|
| 09/783,246 | 02/13/2001 | Michael D. Hutton | ALTRP061/A637 | 1693 |

51501 7590 07/05/2005

BEYER WEAVER & THOMAS, LLP
ATTN: ALTERA
P.O. BOX 70250
OAKLAND, CA 94612-0250

| |
|----------|
| EXAMINER |
|----------|

STEVENS, THOMAS H

| | |
|----------|--------------|
| ART UNIT | PAPER NUMBER |
|----------|--------------|

2123

DATE MAILED: 07/05/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary

Application No.

09/783,246

Applicant(s)

HUTTON, MICHAEL D.

Examiner

Thomas H. Stevens

Art Unit

2123

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --
Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 23 May 2005.
- 2a) ☐ This action is FINAL. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-30 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-30 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
- ☐ Certified copies of the priority documents have been received.
 - ☐ Certified copies of the priority documents have been received in Application No. _____.
 - ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- 1) ☒ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- 3) ☐ Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
Paper No(s)/Mail Date _____
- 4) ☐ Interview Summary (PTO-413)
Paper No(s)/Mail Date: _____
- 5) ☐ Notice of Informal Patent Application (PTO-152)
- 6) ☐ Other: _____

RD

DETAILED ACTION

1. Claims 1-30 were examined.

Section I: Response to Applicants' Arguments (Final Office Action)

Claim Interpretation

2. Examiner acknowledges applicants' response.

35 USC § 102/103

3. Applicants are thanked for addressing this issue; however, Examiner refutes applicants' statements of Hojat's non-disclosure of "a future delay corresponding to a future connection across a boundary" relative to applicants. Examiner's staunch believe this issue is semantics for the same end result. Specifically, applicants arguments are focus future delay; but the Hojat's teaching is, verbosely, the same. Hojat states (column 8, lines 63-67), *"the synthesizer utilizes conventional statistical models to determine the net lengths for nets connecting objects in the same partition"*; the statistical model is used to "anticipate" or predict an event, in this case, the nets lengths for connecting objects, thus predicting an event in the "future".

Applicants' state Hojat doesn't consider timing estimates, which is Hojat clearly states (column 9, lines 32-35): *If the circuit meets timing constraints and partitioning is complete, then the placement driven synthesis process is complete.*

Applicants' state Hojat doesn't teach uncut connections. Hojat does suggest undesired undoing cut connections which suggest uncut connects are a factor within the entire process (column 11, lines 13-16): *In another embodiment of the invention, the*

Art Unit: 2123

placer is provided with an additional step for allowing it to undo a previous cut if the synthesizer performs an undesirable transformation.

Rejection stands.

Section II: RCE (1st Office Action)

Claim Rejections - 35 USC § 102

1. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(e) the invention was described in a patent granted on an application for patent by another filed in the United States before the invention thereof by the applicant for patent, or on an international application by another who has fulfilled the requirements of paragraphs (1), (2), and (4) of section 371(c) of this title before the invention thereof by the applicant for patent.

2. **Claims 1-5,8,10-12, 19, 24 and 30** are rejected under 35 U.S.C. 102(e) as being anticipated by Hojat et al (U.S. Patent Number 6,080,201, excluding “Background of the Invention”), herein referred to as **Hojat A**.

3. As to **Claims 1,19,24 and 30**, **Hojat A** teaches: a method of estimating a critical path delay during a source electronic design placement into a target hardware device, comprising: receiving an electronic representation of the source electronic design (**column 7, lines 46-48 and 56-57**); determining a path criticality in the source electronic design (**column 8, lines 50-61**) based on, determining an actual delay

Art Unit: 2123

corresponding to a connection already placed across a first boundary in the target device (**column 8, lines 30-31, lines 54-60**); determining a statistical estimate for a future delay corresponding to an associated future connection to be placed across a second boundary in the target device (**column 8, line 63-column 9, line 2**); partitioning at least a portion of the source design by placing at least the portion of the source design across boundaries in the target device based on the determined actual delay and the statistical estimate for a future delay (**column 9, lines 7-10**); determining a statistical estimate for a future delay corresponding to an associated future connection to be placed across a second boundary in the target device (**column 8, lines 63-67**) wherein partitions are still large and each partition contains "multiple placeable objects" which, when a future cut is made, the placer attempts to place these multiple objects as partitions become smaller (**column 11, lines 2-5**); partitioning at least a portion of the source design by placing at least the portion of the source design across boundaries in the target device based on the determined actual delay and the statistical estimate for a future delay (**column 9, lines 7-10**); a CPU and a user interface (**column 7, lines 39-46**).

4. As to **Claim 2, Hojat A** teaches placing is biased towards a state in which an individual path having a relatively high criticality is not changed so as to increase an associated delay (**column 9, lines 7-10**) wherein net lengths queried from the placement state data are substituted for statistical net lengths.

Art Unit: 2123

5. As to **Claim 3**, **Hojat A** teaches the placing is biased towards a state in which an individual path having a relatively high criticality is changed in a manner that reduces the associated delay (**column 10, lines 21-26 and Figure 4B and description**).

6. As to **Claim 4**, **Hojat A** teaches the estimate for the future delay is generated by performing partitioning techniques on at least one other electronic source design (**column 7, lines 48-50, 56-59**), wherein the one other electronic source design is the initial placement and synthesis.

7. As to **Claims 5**, **Hojat A** teaches: the electronic representation is received in the form of hardware description language coding (**column 7, line 46**).

8. As to **Claims 8**, **Hojat A** teaches the connections include at least one of conductive lines and switches (**column 4, lines 29-31**).

9. As to **Claim 10**, **Hojat A** teaches iteratively repeating (**Figure 2, elements 204-216**) the determining a path criticality (**Figure 2B, element 208 and 210**) and the partitioning at least a portion of the source design (**Figure 2B, element 204**).

10. As to **Claim 11**, **Hojat A** teaches determining whether to repartition the at least a portion of the source design after the partitioning (**column 9, lines 19-24 and 33-35**); and if necessary, adjusting the estimates of delays from future partitions (**column 11, lines 1-2**) wherein estimated values that were used previously for unplaced portions of the design can be adjusted by using actual delays of objects that have now been placed.

11. As to **Claim 12**, **Hojat A** teaches adjusting the estimates of delays from future partitions comprises: substituting a percentage of delays attributed to the partition in the

Art Unit: 2123

statistical estimate with a new percentage derived from the critical path delay results from the partition (**Figure 2B, repetition of elements 204-216 and column 11, lines 1-2**) wherein the new netlist is used that accounts for actual net lengths of newly placed elements in the design, thereby reducing the percentage of statistical estimates that are needed to model yet-unplaced portions of the design.

Claim Rejections - 35 USC § 103

12. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

13. The factual inquiries set forth in *Graham v. John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:

1. Determining the scope and contents of the prior art.
2. Ascertaining the differences between the prior art and the claims at issue.

Art Unit: 2123

3. Resolving the level of ordinary skill in the pertinent art.
 4. Considering objective evidence present in the application indicating obviousness or nonobviousness.
14. **Claims 6,7 and 9** are rejected under 35 U.S.C. 103(a) as being unpatentable over **Hojat A** as applied to **Claim 1** above, and further in view of Lee (U.S. Patent Number 6,367,056), herein referred to as **Lee**.
15. As to **Claim 6 and 7**, **Hojat A** teaches the electronic design representation is received in the form of a hardware description language and a netlist (**column 7, lines 46-47**).
16. **Hojat A** does not expressly teach the electronic representation is received in the form of a schematic electronically captured.
17. **Lee** teaches the electronic design of an electronic device may exist in various states or stages such as a schematic (**column 5, lines 53-61**).
18. It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the electronic design representations as taught in **Hojat A** to include a schematic representation since electronic design representations can exist in various states or stages as taught in **Lee (column 5, lines 53-61)**.
19. As to **Claim 9**, **Hojat A** teaches that the behavioral model is mapped to a "specific technology" that implements a design encoded in hardware description language (**column 14, lines 12-13, lines 62-64**).
20. **Hojat A** does not expressly teach the target hardware device or "specific technology" is selected from a group comprising: a complex programmable logic device

Art Unit: 2123

(CPLD), a field programmable gate array (FPGA), an application specific integrated circuit (ASIC), a programmable logic device, a general purpose microprocessor, and a board level circuit implementation.

21. **Lee** teaches the target hardware device is selected from a group comprising: a complex programmable logic device (CPLD) (**column 1, lines 27-28**), a field programmable gate array (FPGA) (**column 1, line 26**), an application specific integrated circuit (ASIC) (**column 1, lines 24-25**), a programmable logic device (**column 1, lines 27-28**), a general purpose microprocessor (**column 1, lines 23**), and a board level circuit implementation (**column 6, line 12**) since these are examples of "target hardware devices" which implement an electronic design that may be encoded in a hardware description language (**column 5, lines 53-60**).

22. It would have been obvious to one of ordinary skill in the art at the time the invention was made that the target hardware as taught in **Hojat A** could be chosen from a list containing CPLDs, FPGAs, ASICs, PLDs, general purpose microprocessors and board circuit level implementations since these are examples of "target hardware devices" which implement an electronic design that may be encoded in a hardware description language as taught in **Lee** (**column 5, lines 53-60**).

23. **Claim 12** is rejected under 35 U.S.C. 103(a) as being unpatentable over **Hojat A** as applied to **Claims 1 and 11** above, and further in view of **Hojat et al** (U.S. Patent Number 6,080,201, "Background of the Invention"), herein referred to as **Hojat B**.

24. As to **Claim 12**, **Hojat A** teaches determining whether to repartition at least a portion of the source electronic design based on timing requirements (**column 9, lines**

Art Unit: 2123

10-12, 39-42, column 10, 59-61) wherein timing requirements must be met before the design is re-partitioned.

25. **Hojat A** fails to teach checking the timing requirements by comparing the critical path delays resulting from the partitioning cut with the estimate of critical path delays prior to the partitioning cut.

26. **Hojat B** teaches a method for determining whether a design meets timing criteria that determine whether to repartition at least a portion of the source electronic design by comparing the critical path delays resulting from the partitioning cut with the estimate of critical path delays prior to the partitioning cut wherein the "actual delay time" is the critical path delays resulting from the partitioning cut and "designed delay time" is the estimate of critical path delays prior to the partitioning cut (**column 3, line 61-column 4, line 5**) since the propagation delay time for a path as designed by the synthesizer is often different than the actual delay time of the path after the placement has placed it in the image (**column 3, lines 62-66**).

27. It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the checking timing requirements as taught in **Hojat A** with the checking of timing requirements as taught in **Hojat B** since the propagation delay time for a path as designed by the synthesizer is often different than the actual delay time of the path after the placement has placed the design in the image as taught in **Hojat B**.

Art Unit: 2123

28. **Claims 14-18, 20-23 and 25-29** are rejected under 35 U.S.C. 103(a) as being unpatentable over **Hojat A** as applied to **Claims 1,19,24 and 30** above, and further in view of Curtin et al (U.S. Patent Number 5,237,514), herein referred to as **Curtin**.

29. As to **Claims 14-18, 20-23 and 25-29**, **Hojat A** teaches: the statistical estimate for future delay comprises: receiving at least one source design (**column 7, lines 46-48 and 56-57**); placing the at least one source design using partitioning methods to place the device across boundaries in the target device (**column 8, lines 19-25 and 30-32**) and determining a statistical estimate for a future delay corresponding to an associated future connection to be placed across a second boundary in the target device (**column 8, line 63-column 9, line 2**).

30. **Hojat A** does not expressly teach generating statistical data corresponding to each type of boundary crossed in the target device wherein the statistical data represents the proportion of each hierarchical type of cut of the entire number of cuts in the fully placed design, the statistical estimates correspond to the weighted average of the statistical data generated, the weighted average is based on a predetermined number or percentage of the slowest delays, or the weighted average is based on a predetermined number or percentage of the fastest delays.

31. As to **Claims 14,15,20,25 and 26**, **Curtin** teaches generating statistical data corresponding to each type of boundary crossed in the target device wherein the statistical data represents the proportion of each hierarchical type of cut of the entire number of cuts in the fully placed design (**column 5, lines 58-column 6, lines 11**) wherein the net segment slack constitutes the delay value of the type of cut and the

Art Unit: 2123

contribution presence factor will provide the proportion of each hierarchical type of cut in the path. **Curtin** teaches this method to determine an approximation for an initial placement procedure that appropriately reflects the complexity of path interaction requirements and net slack tailoring in the positioning and partitioning of blocks (column 5, lines 31-33 and 39-44).

32. As to **Claims 16,21 and 27**, **Curtin** teaches the statistical estimates correspond to the weighted average of the statistical data generated (column 5, line 60 and lines 10-11).

33. As to **Claims 17,18,22,23,28 and 29**, it is concluded that the "net contribution factor" as taught in **Curtin** would allow the proportion, or percentage of fastest or slowest delays to be represented (column 5, lines 60-63). Since these equations are solved to give a per "net segment" delay or slack contribution (column 6, lines 22-24), it is determined that the contribution, or presence factor, "k" is a pre-determined value. Therefore, the weighted average as disclosed in **Curtin** is based on a predetermined number of the fastest and slowest delays.

34. It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the statistical estimate as taught in **Hojat A** with generating statistical data corresponding to each type of boundary crossed in the target device wherein the statistical data represents the proportion of each hierarchical type of cut of the entire number of cuts in the fully placed design as taught in **Curtin** since **Curtin's** method determines an approximation for the initial placement procedure that

Art Unit: 2123

appropriately reflects the complexity of path interaction requirements and net slack tailoring in the positioning and partitioning of blocks (column 5, lines 31-33 and 39-44).


Correspondence Information

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Mr. Tom Stevens whose telephone number is 571-272-3715, Monday-Friday (8:00 am- 4:30 pm) or contact Supervisor Mr. Leo Picard at (571) 272-3749. Fax number is 571-273-3715.

Any inquiry of a general nature or relating to the status of this application should be directed to the TC 2100 Group receptionist: 571-272-2100.

June 29, 2005

THS


Paul L. Rodriguez 7/1/05
Primary Examiner
Art Unit 2125